



A stylish and compact wall mounting Single Sided LED Exit Sign that can either be surface or semi-recessed mounted. This unit is available in either a Switchable Maintained/Non-Maintained or a DALI Self-Test version.

The unit comes with a Plexi glass screen printed legend plate which offers an impressive 30m viewing distance. The legend panels are available in either Arrow Down (AD), Arrow Left (AL) or Arrow Right (AR).

The batteries used with this unit not only offer double the life of traditional emergency lighting batteries, but consume far less power during their operation.

- 2W / 3W
- Surface Mount (Wall)
- White Polycarbonate Body
- Extra Long Life LiFePO4 cells
- Ingress Protection Rating - IP40 rated
- 30m Viewing Distance
- ISO Legends as Standard
- DDP (Deep Discharge Protection)
- Samsung LEDs

CODE <small>XX (Configurable Option)</small>	DESCRIPTION	CONFIGURABLE OPTION (XX)
ELP-2-M-T2-XX	SWITCHABLE MAINTAINED	AD ARROW DOWN
ELP-3-NM-T3-XX	NON-MAINTAINED, DALI, SELF TEST	AL ARROW LEFT
		AR ARROW RIGHT

Technical Details

	ELP-2-M-T2-XX	ELP-3-NM-T3-XX
Mains Supply	230-240 Volts 50/60Hz	
Power Rating	44mA $\lambda = 0.6$	37mA $\lambda = 0.61$
Duration	3 Hours	
Recharge Period	12 Hours – Energy saving electronic charger	
Battery Size & Type	6.4V 3.0Ah LiFePO4 Cells	9.6V 1.5Ah LiFePO4 Cells
Charge Current	0-400mA Float	0-150mA Float
Battery Current Limit	700mA	350mA
Ingress Protection Rating	IP40	
Class	Class II	
Warranty	4 Years	