



The ENN2 is a high output emergency LED bulkhead which is designed for high ceiling applications.

The high output LED strip use in this fitting provides 950 lumens after the diffuser in mains operation and 600 lumens in emergency operation, making this perfect for warehouse applications.

- 5W
- IP65 Ingress Protection
- Standard and DALI Self-Test Options Available
- 950 Lumen in Mains Operation
- 600 Lumen in Emergency Operation
- Suitable for High Ceilings
- Makrolon Diffuser with High LOR
- Extra Long Life LiFePO4 Batteries

Spacing Table:

Mounting Height	Axial to Wall		Axial to Axial		Transverse to Axial		Transv. to Transv.		Transverse to Wall	
	0.5 Lux	1.0 Lux	0.5 Lux	1.0 Lux	0.5 Lux	1.0 Lux	0.5 Lux	1.0 Lux	0.5 Lux	1.0 Lux
2.5m	2.9m	2.3m	9.7m	7.0m	10.9m	8.5m	13.2m	11.2m	5.6m	4.5m
3.0m	3.0m	2.5m	8.3m	6.0m	11.4m	9.1m	14.5m	12.2m	6.1m	4.6m
4.0m	3.4m	2.5m	8.4m	6.8m	12.6m	9.9m	16.7m	13.0m	6.5m	4.8m
5.0m	3.6m	2.4m	9.0m	7.1m	13.4m	10.3m	17.9m	13.4m	6.7m	4.3m
6.0m	3.6m	1.5m	9.8m	7.2m	14.2m	10.3m	18.6m	13.4m	6.7m	2.6m
8.0m	2.7m	-	10.1m	5.3m	14.7m	7.2m	19.2m	9.1m	4.5m	-

CODE	DESCRIPTION
ENN2-5-M-T1	MAINTAINED
ENN2-5-NM-T3	NON-MAINTAINED, DALI, SELF TEST
ENN2-5-NM-T1	NON-MAINTAINED

ACCESSORIES
CODE Description
ENN-LG-KIT ADHESIVE LEGEND KIT FOR: ARROW UP, ARROW DOWN, ARROW LEFT & ARROW RIGHT

Technical Details

Mains Supply	230-240 Volts 50/60Hz
Power Rating (Non-maintained)	23mA λ = 0.88mA 5W
Duration	3 Hours
Battery Size & Type	6.4V 3.8Ah LiFePO4
Rating	IP65
Lumen Output	600 lumens in emergency; 950 lumens in mains
Beam Angle	125° x 117°
Light Source Colour Temp.	4000K
Ta	25°
Dimensions	370mm x 140mm x 89mm
Mains Input Terminal	0.5mm x 2.5mm Cable
Weight	2.1Kg