



The ERS is a stylish and compact IP65 rated 3 Watt LED luminaire suitable for mounting a number of different ways. The unit is available in either a Switchable Maintained, Non-Maintained or DALI Self-Test version.

The fitting is not only more compact than the majority of LED bulkheads, but offers an impressive 350 lumens. The batteries used with this unit not only offer double the life of traditional emergency lighting batteries, but consume far less power during their operation.

- 3W
- Surface Mount (Wall or Ceiling)
- Optional Recessed (Wall or Ceiling)
- Optional Pendant (Ceiling)
- White Polycarbonate body
- Translucent Polycarbonate Cover
- Extra Long Life LiFePO4 cells
- Ingress Protection Rating - IP65
- DDP (Deep Discharge Protection)
- Samsung LEDs

CODE	DESCRIPTION
ERS-3-M-T2	SWITCHABLE MAINTAINED
ERS-3-NM-T1	NON-MAINTAINED
ERS-3-NM-T3	NON-MAINTAINED, DALI, SELF TEST

ACCESSORIES
CODE <i>Description</i>
ERS-LG-KIT ADHESIVE LEGEND KIT FOR: ARROW UP, ARROW DOWN, ARROW LEFT & ARROW RIGHT

Technical Details

Mains Supply	230-240 Volts 50/60Hz
Power Rating	55mA $\lambda = 0.6$ Maintained 25mA $\lambda = 0.6$ Maintained
Duration	3 Hours
Recharge Period	12 Hours – Energy saving electronic charger
Battery Size & Type	6.4V 3.0Ah LiFePO4 Cells
Charge Current	Dual Rate Charge 0-400mA
Battery Current Limit	1000mA
Ingress Protection Rating	IP65
Light Output	3W
Light Source	8 pcs Samsung LED
LED Source	350 Lumens (LDT files available)
Warranty	4 Years